



*A low phosphate, highly caustic liquid compound formulated to be used in foaming devices to remove baked-on grease, smoke and tar from smokehouses, walls, bacon hooks and other greasy surfaces.*

**Directions:** Apply Liquid Foam XX inside and outside of smoke house or on other surfaces with foaming devices. Let foam remain on surface until it begins to slide off. Then rinse with clean water.

The Quality Chemical Company   
**VentureTECH**  
CORPORATION

10720 Lexington Drive • Knoxville, TN 37932  
(865) 966-2532 • 1-800-826-4095 • FAX (865) 675-2532

# LIQUID FOAM XX

**WARNING: Harmful if Swallowed:** Corrosive to mouth, throat, esophagus and stomach. **Avoid Breathing Dust or Mists:** Corrosive to mucous membranes of the respiratory tract. **Avoid Eye Contact: Corrosive to eyes:** Burns eye tissue, cornea and retina. **Avoid Contact With Skin:** Corrosive to skin, causes severe & rapid burns, destructive to tissues on contact. **PERSONAL PROTECTION:** Wash thoroughly after use. Use with adequate ventilation. Chemical type goggles recommended. Impervious rubber or neoprene gloves recommended. **First Aid: INHALATION-**Get to fresh air. **EYES-**Flush with plenty of water for at least 15 minutes. See a physician. **INGESTION-** Do not induce vomiting. If conscious drink plenty of water. Call a physician or poison control center immediately. **SKIN-**Flush with plenty of water. **READ THE MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT.**

**KEEP OUT OF REACH OF CHILDREN**

MEMBER  
**ISSA**

**HMS RATING**

|   |               |
|---|---------------|
| 0 | Fire Hazard   |
| 3 | Health Hazard |
| 1 | Reactivity    |

0 - None  
1 - Slight  
2 - Moderate  
3 - High  
4 - Severe