



A CONCENTRATED, INHIBITED, LIQUID ALKALINE CLEANER WITH LOW SUDSING ACTION. FOR PRESSURE OR SOAK CLEANING OF MOTORS, PARTS, FLOORS, EQUIPMENT AND MACHINERY. ALSO REMOVES HEAVY GREASE, RUBBER MARKS AND SOILS FROM CONCRETE.

Use dilution depending on surfaces and soiled conditions.

**AVERAGE SOIL-** USE 3 to 6 OUNCES PER GALLON OF WATER

**HEAVY SOIL-** USE 10 TO 20 OUNCES PER GALLON OF WATER.

The Quality Chemical Company   
**VentureTECH**  
CORPORATION

10720 Lexington Drive • Knoxville, TN 37932  
(865) 966-2532 • 1-800-826-4095 • FAX (865) 675-2532

# "LOW FOAM" G-37

## Heavy Duty Alkaline Concentrate

**WARNING: Harmful if Swallowed:** Corrosive to mouth, throat, esophagus and stomach. **Avoid Breathing Dust or Mists:** Corrosive to mucous membranes of the respiratory tract. **Avoid Eye Contact: Corrosive to eyes:** Burns eye tissue, cornea and retina. **Avoid Contact With Skin:** Corrosive to skin, causes severe & rapid burns, destructive to tissues on contact. **PERSONAL PROTECTION:** Wash thoroughly after use. Use with adequate ventilation. Chemical type goggles recommended. Impervious rubber or neoprene gloves recommended. **First Aid: INHALATION-** Get to fresh air. **EYES-** Flush with plenty of water for at least 15 minutes. See a physician. **INGESTION-** Do not induce vomiting. If conscious drink plenty of water. Call a physician or poison control center immediately. **SKIN-** Flush with plenty of water. READ THE MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT.

**KEEP OUT OF REACH OF CHILDREN**

MEMBER  
**ISSA**

HMIS RATING

Fire Hazard	0
Health Hazard	2
Reactivity	0

0 - None  
1 - Slight  
2 - Moderate  
3 - High  
4 - Severe