



**A BLEND OF WETTING AGENTS WHICH ACTUALLY BREAK THE MAGNETIC FILM PRIOR TO WASHING. THIS PRE-SOAK METHOD GREATLY IMPROVES CLEANING PERFORMANCE IN ANY CARWASH OPERATION.**

**Directions:** Make stock solution containing 1-2 gallons per 55 gallons of water. Mix into system to provide a light foam on the car surface. Cover the entire car with pre-soak cleaning solution. Proceed with normal washing procedures.

The Quality Chemical Company   
**VentureTECH**  
CORPORATION

10720 Lexington Drive • Knoxville, TN 37932  
(865) 966-2532 • 1-800-826-4095 • FAX (865) 675-2532

# AUTO STAGE #2

**HIGH FOAMING CONCENTRATED PRE-SOAK LIQUID**

**WARNING: Harmful if Swallowed:** Corrosive to mouth, throat, esophagus and stomach. **Avoid Breathing Dust or Mists:** Corrosive to mucous membranes of the respiratory tract. **Avoid Eye Contact:** *Corrosive to eyes:* Burns eye tissue, cornea and retina. **Avoid Contact With Skin:** Corrosive to skin, causes severe & rapid burns, destructive to tissues on contact. **PERSONAL PROTECTION:** Wash thoroughly after use. Use with adequate ventilation. Chemical type goggles recommended. Impervious rubber or neoprene gloves recommended. **First Aid: INHALATION-**Get to fresh air. **EYES-**Flush with plenty of water for at least 15 minutes. See a physician. **INGESTION-**Do not induce vomiting. If conscious drink plenty of water. Call a physician or poison control center immediately. **SKIN-**Flush with plenty of water. READ THE MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT.

**KEEP OUT OF REACH OF CHILDREN**

MEMBER  
**ISSA**

**HMS RATING**

0	0
3	0

Health Hazard      Fire Hazard      Reactivity

- 0 - None
- 1 - Slight
- 2 - Moderate
- 3 - High
- 4 - Severe