



**A blend of wetting agents which actually break the magnetic film prior to washing. This pre-soak method greatly improves cleaning performance in any car-washing operation.**

**Directions:** Make stock solution containing 1-2 gallons per 55 gallons of water. Mix into system to provide a light foam on the car surface. Cover the entire car with pre-soak cleaning solution. Proceed with normal washing procedures.

# PRE SOAK

**HIGH FOAMING  
CONCENTRATED LIQUID**

**WARNING: Harmful if Swallowed:** Irritant to mouth, throat, esophagus and stomach. **Avoid Breathing Dust or Mists:** Irritant to mucous membranes of the respiratory tract. **Avoid Eye Contact:** Irritant to eye tissues. **Avoid Contact with Skin:** Irritant to all skin tissues. **PERSONAL PROTECTION:** Wash thoroughly after use. Use with adequate ventilation. Chemical type goggles recommended. Impervious rubber or neoprene gloves recommended. **First Aid: INHALATION-** Get to fresh air. **EYES-** Flush with plenty of water for at least 15 minutes. See a physician. **INGESTION-** Do not induce vomiting. If conscious drink plenty of water. Call a physician or poison control center immediately. **SKIN-** Flush with plenty of water. **READ THE MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT.**

**KEEP OUT OF REACH OF CHILDREN**

The Quality Chemical Company   
**VentureTECH**  
CORPORATION  
10720 Lexington Drive • Knoxville, TN 37932  
(865) 966-2532 • 1-800-826-4095 • FAX (865) 675-2532

MEMBER  
**ISSA**

HMIS RATING

Health Hazard	1	0	0	Fire Hazard	0	0
					0 - None	0 - None
					1 - Slight	1 - Slight
					2 - Moderate	2 - Moderate
					3 - High	3 - High
					4 - Severe	4 - Severe